



GEGRÜNDET 1928

# ACTIVE COLOR 250W

ACTIVE COLOR is a compact and dynamic projector suitable for a wide range of many applications, it's a colour changer, image projector and strobe effect

## FEATURES

- Suitable from 2mt to 10mt distance
- Compact and dynamic
- Complies to CE standards

## MECHANICAL DATA

- Aluminium and steel body
- Black (standard) epoxy powder paint
- Bracket for adjustable fixing
- Can be installed in any position
- Rear safety chain hook
- Ta max (in-door) 35°C
- Little fan



PF09009 ACTIVE COLOUR 250W

## TECHNICAL DATA

- Supply voltage: 230V 50Hz (60Hz specified option)
- Rated current: 3.2A at 230V
- Socket GY 9.5 for HSD/MSD 250 discharge lamp
- Lamp access at the rear of the projector
- High efficiency parabolic reflector
- Two focusing lenses
- Adjustable focusing (manual)
- 1.2mt cable with plug
- Cable clamp and built-in fuse
- 3 Pin panel connectors (in/out) for DMX
- Colour wheel with 11 colours plus white
- Effect wheel with 4 correction filter, 2 interchangeable metal gobos (OD27mm IA22mm), 3 spot diameter and frost diffuser filter
- Linear dimmer from 0 to 100%
- Very fast shutter strobe
- Musical function, sound activated
- Intelligent control panel with dip-switches
- It works via DMX512 signal (4 channels) or in stand alone mode (automatic pre-programmed sequences or sound-activated mode)

## **STENGER – TECHNIK Ihr Partner für Licht**

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GESELLSCHAFT M.B.H.

Sebastianplatz 2,  
A-1030 Wien

Tel: +43/1/712-45-99-0

Fax: +43/1/712-45-99-10

E-Mail: office@stenger-technik.com



# ACTIVE COLOR 250W



GEGRÜNDET 1928

## DMX CHANNELS

- 1 Shutter - 2 Dimmer - 3 Colours - 4 Effects

## BEAM ANGLE

- 23° without frost
- 45° with frost

## IMAGE DIAMETER

- 2m at 5m distance without frost
- 4.6m at 5m distance with frost

## LUX

- 1000 Lux at 5m without frost
- 450 Lux at 5m with frost

## ORDER CODES

- LP68 HSD/MSD 250W GX9.5 lamp - 2000h

### **STENGER – TECHNIK Ihr Partner für Licht**

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GESELLSCHAFT M.B.H.

Sebastianplatz 2,  
A-1030 Wien

Tel: +43/1/712-45-99-0

Fax: +43/1/712-45-99-10

E-Mail: [office@stenger-technik.com](mailto:office@stenger-technik.com)

