

HF Wireless Remote Control

for PHOENIX (XT), MENTOR and VISION 10



HF Wireless remote control system for PHOENIX (XT), MENTOR and VISION 10 lighting control desks. The receiver connects to the desks' EIA/RS-232 serial port.

The system permits to:

- select channels individually or in groups and attribute intensities in %, at 100%, at 0%
- call / retrieve memories and groups
- clear the last operation
- erase selections
- remote control the playback (GO, CUT)
- call macros (pre-programmed)
- activate the BLACK-OUT function
- test and isolate individual channels (TEST)

Technical Characteristics

Operating range	: 75-200 m depending on the environment
Frequency	: 433.92 MHz (license free)
Approvals	: ETSI 800-220 European Regulations compliant
Power Output	: 10 mW
Transmission speed	: 9600 baud
Connection to desk	: EIA/RS-232

This equipment complies with all applicable European directives and carries a CE mark.

HF Wireless Remote Control

Receiver + transmitter

Characteristics:

Transmitter

Batteries : Alkaline, 9 Volt (6F22)
 Expected operational life: 1 year

Dimensions (mm) : 115 x 60 x 20 (excl. aerial)
 Weight (g) : 280 (incl. battery)

Receiver

Supply voltage : 230 V and 115 V (switchable),
 +/10%, 50 / 60 Hz
 Power consumption : 3 VA
 Mains Fuse : internal, automatic reset

Dimensions (mm) : 200 x 44 x 150 (W x H x D) (excl. aerial)
 Weight (kg) : 1.4

STENGER - TECHNIK - Your Partner for Light

ISO 9001 : 2000 Certified

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GES.M.B.H.

Sebastianplatz 2
 A - 1030 Wien
 AUSTRIA

Tel.: +43 / 1 / 712 45 99 - 0
 Fax: +43 / 1 / 712 45 99 - 10
 Mail: office@stenger-technik.com

ADB
 Lighting Technologies

DS-2113-E-09g Subject to modifications