



GEGRÜNDET 1928

HYPER COLOR 575W

FEATURES

- Soft beam colour changer
- Suitable from 2mt to 20mt distance
- CYM (Cyan - Yellow - Magenta) colour mixing system for infinity colour combination
- Linear dimmer from 0 to 100%
- Fast Strobe - black-out
- Complies to CE standards

MECHANICAL DATA

- Aluminium and steel body
- Black (standard) epoxy powder paint
- Bracket for adjustable fixing
- Can be installed in any position
- Lateral safety chain hook
- Ta max (in-door) 35°C
- Silent fan



PF09004 HYPER COLOR 575W

TECHNICAL DATA

- Supply voltage: 230V 50Hz (60Hz optional)
- Rated current: 4.1A at 230V (pfc)
- Socket GX 9.5 for MSR/MSD 575 discharge lamp
- Lamp access to remove the top lid
- High efficiency parabolic reflector
- In-built anti-IR lens
- Special lens diffuser
- 1.2mt cable not terminated
- Cable clamp, rear panel fuse
- 3 Pin panel connectors (in/out) for DMX
- Intelligent control panel with dip-switches
- Works via DMX512 signal (6 channels) or in complete stand alone mode

ORDER CODES

- PF09011 4 leaves barn-doors
- PF09016 Spot adapter (zoom from 10° to 25°)
- LP77 HSR/MSR 575W GX9.5 lamp
- PF95021 PROFESSIONAL FLIGHT CASE for 3 HYPERCOLOR 575W

STENGER – TECHNIK Ihr Partner für Licht

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GESELLSCHAFT M.B.H.

Sebastianplatz 2,
A-1030 Wien

Tel: +43/1/712-45-99-0

Fax: +43/1/712-45-99-10

E-Mail: office@stenger-technik.com

