



GEGRÜNDET 1928

MOVING SPOT 1200W

FEATURES

- High efficiency moving head projector
- Suitable from live show and disco
- Complies to CE standards^

MECHANICAL DATA

- Pan 450° - Tilt 255°
- PAN-TILT locked system
- Black (standard) epoxy powder paint
- Can be installed in any position
- 53Kg 641x621x696mm



PF09013 MOVING SPOT 1200W

TECHNICAL DATA

- Supply voltage: 230V 50 or 60Hz (to be specified when ordering)
- Rated current: 7A at 230V with p.f.c. and fuse
- HMI 1200/S discharge lamp, DE short
- Socket SFc 10-4
- High efficiency optical system (double condenser optics)
- Intelligent control panel with LED display and rotating switches
- Works via DMX512 signal (16 or 20 channels)

EFFECTS

- Colour wheel (7+open)
- C.Y.M. colour mixing system
- Rotating gobo wheel (4+open)
- Fixed gobo wheel (4+open)
- Frost filter
- Dimmer, black-out
- Iris diaphragm
- Rotating prism wheel (4+open)
- Linear zoom from 12° to 23°
- Pan, tilt, speed control

ORDER CODES

- LP117 HMI 1200/S short DE SFc 10-4

STENGER – TECHNIK Ihr Partner für Licht

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GESELLSCHAFT M.B.H.

Sebastianplatz 2,
A-1030 Wien

Tel: +43/1/712-45-99-0

Fax: +43/1/712-45-99-10

E-Mail: office@stenger-technik.com

