



GEGRÜNDET 1928

# TINTORETTO 1200W

## FEATURES

- Fantastic 1200W discharge lamp centrepiece
- Single source, 6 powerful out-put, PAN/TILT
- Suitable over 10mt height
- Complies to CE standards

## MECHANICAL DATA

- Aluminium and steel body projector
- Black (standard) epoxy powder paint
- Aluminium bracket for adjustable fixing
- Designed for disco and show business
- Ta max (in-door) 35°C
- Projector with fan
- The arms are furnished in separate package

## TECHNICAL DATA

- 230V 50 or 60Hz (to be specified when ordering)
- Rated current 8A at 230V (16A fuse)
- Magnetic ballast (external box)
- Socket G22
- Tilt angle range 100°
- PAN angle range 144°
- Lamp access at bottom of the projector
- 6 double optic condensers
- Manual adjustable focusing
- Cable not terminated (ballast)
- 2m cable with plug (projector-ballast)
- Intelligent control panel with 4-digit LED display
- Works via DMX512 signal (10 channels 8Bit) or in stand alone mode (automatic or music mode ON/OFF)
- Remote black-out with projector in stand-alone mode
- Dmx 3 Pin connectors are included
- Rotating mirror accessory is included

## SPECIFICATIONS

- The tilt and pan positions run in pair of arms
- The strobe/black out run in pair of arms
- 3 levels of superimposed coloured gobos with 6 gobos on each level

## DMX CHANNELS

- 1 PAN arms 1 and 4, 2 TILT arms 1 and 4, 3 PAN arms 2 and 5, 4 TILT arms 2 and 5, 5 PAN arms 3 and 6, 6 TILT arms 3 and 6, 7 COLOURED GOBOS selection (3 levels), 8 SHUTTER/STROBE arms 1 and 4, 9 SHUTTER/STROBE arms 2 and 5, 10 SHUTTER/STROBE arms 3 and 6

## ORDER CODES

- LP38 MSR/HSR lamp G22 socket



AS110/P TINTORETTO 1200W pan/tilt

## **STENGER – TECHNIK Ihr Partner für Licht**

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GESELLSCHAFT M.B.H.

Sebastianplatz 2,  
A-1030 Wien

Tel: +43/1/712-45-99-0

Fax: +43/1/712-45-99-10

E-Mail: office@stenger-technik.com

