



GEGRÜNDET 1928

UNDERGROUND DISCHARGE

FEATURES

- Adjustable down-light colour changer
- Colour wheel (6colours + white) with continuous rainbow effect
- Suitable for architectural applications
- Complies to CE standards

MECHANICAL DATA

- Aluminium body
- Grey and black epoxy powder paint, resistant to the agents atmospherics
- IP67 protection rate
- Temperate glass 20mm (up load 2000Kg vehicles)
- Ring 250mm, height 340mm
- Plastic house on request (220x375mm)



AS149 UNDERGROUND DISCHARGE 35W IP67

TECHNICAL DATA

- Supply voltage: 230V 50 or 60Hz (to be specified when ordering)
- Rated current: 0.4A at 230V (pfc)
- Built-in fuse
- Socket G12
- High efficiency reflector
- Adjustable flux direction +/- 5°
- Built-in terminal connector block
- Works via DMX512 signal or in stand alone mode (sequences and timing select directly from the projector with MASTER/SLAVE function)

LAMP TYPES

- CDM-T 35W G12 (3000K - 12000h) or similar

STENGER – TECHNIK Ihr Partner für Licht

ING. STENGER • ELEKTROTECHNISCHE UND BÜHNENBELEUCHTUNGSGERÄTE GESELLSCHAFT M.B.H.

Sebastianplatz 2,
A-1030 Wien

Tel: +43/1/712-45-99-0

Fax: +43/1/712-45-99-10

E-Mail: office@stenger-technik.com

